

# Solar Battery

## B1-5.1-48

**SAJ**



Modular Design



Excellent Protection



Easy Installation



Safest Chemistry



Long Lifespan

### B1-5.1-48 Datasheet

Type	B1-5.1-48
<b>Electrical Characteristics</b>	
Total Energy Capacity [Wh]	5120
Usable Capacity [Wh]	4600
Rated Voltage [V]	51.2
Voltage range [V]	42~58.4
Depth Of Discharge [DOD]	≤90%
Cycle Life	≥6000
Max.Charge Current [A]	60
Max.Discharge Current [A]	60
<b>Physical Parameters</b>	
Battery Type	Lithium ion
Communication	CAN
Operating Temperature Range	0°C~50°C
Cooling Method	Natural Convection
Ambient Humidity	0-95% Non-condensing
Ingress Protection	IP65
Dimensions [H*W*D][mm]	410*650*186
Weight [kg]	48
Standard Warranty [Year]	5 (Standard) /10 (Optional)
Applicable Standard	UN38.3、IEC 62619

### GUANGZHOU SANJING ELECTRIC CO., LTD.

Website: [www.saj-electric.com](http://www.saj-electric.com)

E-mail: [info@saj-electric.com](mailto:info@saj-electric.com)

Add:SAJ Innovation Park, No.9, Lizhishan Road, Science City, Guangzhou, Guangdong, P.R.China.

